NSN 5305-01-007-7055



Socket Head Cap Screw - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5305-01-007-7055 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.297 inches and 0.391 inches **Fastener Length:** Between 0.359 inches and 0.391 inches **Head Style: Button Head Diameter:** Between 0.250 inches and 0.262 inches **Head Height:** Between 0.063 inches and 0.073 inches **Spline Minor Diameter:** Between 0.080 inches and 0.082 inches **Spline Major Diameter:** Between 0.097 inches and 0.098 inches **Spline Width:** Between 0.021 inches and 0.022 inches **Internal Drive Style:** Six spline **Thread Diameter:** 0.138 inches Thready Qty Per Inch (tpi): 32 Material: Steel comp 301 or steel comp 302 or steel comp 303 or steel comp 303 or steel comp 303 or steel comp 304 or steel comp 304I or steel comp 305 or steel comp 308 or steel comp 309 or steel comp 309 or steel comp 310 or steel comp 310 or steel comp 310 or steel comp 309 or steel comp 300 or steel comp comp 310s or steel comp 314 or steel comp 316 or steel comp 316l or steel comp 317 or steel comp 321 or steel comp 323 or steel comp 324 or steel comp 347 or steel comp 348 or steel comp 385 **Material Specification:** 66 federal standard all material responses **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unc

Demilitarization:

Unit Of Measure:

Shelf Life:

N/a

NSN 5305-01-007-7055

Socket Head Cap Screw - Page 2 of 2



Fiig:

A003b0