NSN 5305-01-007-8429

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-007-8429 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.459 inches and 0.526 inches **Fastener Length:** Between 1.219 inches and 1.266 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.499 inches and 0.507 inches **Grip Diameter:** Between 0.3110 inches and 0.3120 inches **Internal Drive Style:** Offset cruciform (torque set) **Thread Diameter:** 0.250 inches **Grip Length:** Between 0.740 inches and 0.760 inches Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 180000 pounds per square inch Hardness Rating: 39.0 rockwell c and 43.0 rockwell c **Countersink Angle:** 100.0 degrees Surface Finish: 32.0 microinches grip Material: Steel comp e4340 or steel comp 4140 or steel comp 4340 or steel comp 8740 **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Qq-p-416, type 2, class 2 federal specification single treatment response **Thread Series Designator:** Unf Shelf Life: N/a

--

Unit Of Measure:

NSN 5305-01-007-8429

Close Tolerance Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0