NSN 5305-01-008-2892

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-008-2892 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.400 inches and 0.467 inches **Fastener Length:** Between 0.972 inches and 1.019 inches **Head Style:** Pan **Head Diameter:** Between 0.473 inches and 0.492 inches **Head Height:** Between 0.162 inches and 0.175 inches **Hole Diameter:** 0.037 inches **Grip Diameter:** Between 0.2485 inches and 0.2495 inches **Internal Drive Style:** High-torque **Thread Diameter:** 0.250 inches **Grip Length:** Between 0.552 inches and 0.572 inches **Hole Quantity:** 1 **Hole Type:** Drilled Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 160000 pounds per square inch **Surface Finish:** 63.0 microinches grip **Product Name:** Navy special project Material: Titanium alloy uns r54520

Material Specification: Nas621, comp 6al-4v assn standard single material response **Thread Series Designator:** Unf

NSN 5305-01-008-2892

Close Tolerance Screw - Page 2 of 2



_					
٠.	n	_	I+	18	e:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0