

View Online at <https://aerobasegroup.com/nsn/5305-01-008-5403>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.779 inches

Fastener Length:

Between 4.660 inches and 4.676 inches

Head Style:

Round w/wrench flats

Head Diameter:

Between 1.855 inches and 1.875 inches

Head Height:

0.490 inches

Width Between Flats:

Between 1.610 inches and 1.625 inches

Shoulder Diameter:

1.499 inches first shoulder

Shoulder Length:

3.710 inches first shoulder and 3.736 inches first shoulder

Shank Unthreaded Hole Diameter:

0.141 inches first hole and 0.151 inches first hole

Internal Drive Style:

Slot

Thread Diameter:

1.250 inches

Thready Qty Per Inch (tpi):

12

Min. Tensile Strength (psi):

220000 pounds per square inch

Hardness Rating:

46.0 rockwell c and 50.0 rockwell c

Distance From Head Largest Bearing Surface To Shank Hole Center:

4.440 inches first hole

Shoulder Shape:

Round first shoulder

Special Features:

Retaining element in shank

Material:

Steel

Material Specification:

G-1010 comp 4330fscm 26512 mfr ref single material response

Surface Treatment:

Chromium

Surface Treatment Specification:

Qq-c-320 class 2e federal specification single treatment response head

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-c-8837 spec.