

View Online at <https://aerobasegroup.com/nsn/5305-01-008-5404>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.555 inches

Fastener Length:

Between 2.670 inches and 2.706 inches

Head Style:

Round w/wrench flats

Head Diameter:

Between 0.990 inches and 1.000 inches

Head Height:

0.312 inches

Width Between Flats:

Between 0.880 inches and 0.888 inches

Shoulder Diameter:

0.749 inches first shoulder

Shoulder Length:

2.120 inches first shoulder and 2.146 inches first shoulder

Shank Unthreaded Hole Diameter:

0.141 inches first hole and 0.151 inches first hole

Internal Drive Style:

Slot

Thread Diameter:

0.625 inches

Thready Qty Per Inch (tpi):

18

Min. Tensile Strength (psi):

180000 pounds per square inch

Hardness Rating:

39.0 rockwell c and 45.0 rockwell c

Distance From Head Largest Bearing Surface To Shank Hole Center:

2.490 inches first hole

Shoulder Shape:

Round first shoulder

Special Features:

Retaining element in shank

Material:

Steel comp xm-13

Material Specification:

Ams 5629 assn standard single material response

Surface Treatment:

Passivate

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0