Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-008-9296

New Online at https://doi/obd/segroup.com/hol//obd/of 01 000 5250
Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.237 inches and 0.267 inches
Fastener Length:
Between 0.318 inches and 0.421 inches
Head Style:
Flat chamfer
Head Diameter:
Between 0.303 inches and 0.313 inches
Head Height:
Between 0.185 inches and 0.190 inches
Locking Feature:
Patch threads or strip threads
Internal Drive Style:
Hexagon
Thread Diameter:
0.190 inches
Width Across Flats:
Between 0.156 inches and 0.158 inches
Thready Qty Per Inch (tpi):
32
Min. Tensile Strength (psi):
80000 pounds per square inch
Material:
Steel comp 302 or steel comp 303 or steel comp 304 or steel comp 305 or steel comp 316
Material Specification:
66 federal standard all material responses
Surface Treatment:
Passivate
Surface Treatment Specification:
Qq-p-35 federal specification single treatment response
Thread Series Designator:
Unf
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

NSN 5305-01-008-9296

Socket Head Cap Screw - Page 2 of 2

Fiig: A003b0

