Socket Head Cap Screw - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5305-01-009-0019

| Thread C | lass: |
|------------|---|
| 3a | |
| Thread Di | irection: |
| Right-han | d |
| Thread Le | ength: |
| 0.724 inch | nes |
| Fastener | Length: |
| Between (| 0.985 inches and 1.015 inches |
| Head Styl | le: |
| Flat cham | fer |
| Head Dia | meter: |
| Between (| 0.176 inches and 0.183 inches |
| Head Heig | ght: |
| Between (| 0.108 inches and 0.112 inches |
| Internal D | Drive Style: |
| Hexagon | |
| Thread Di | iameter: |
| 0.112 inch | nes |
| Width Ac | ross Flats: |
| Between (| 0.094 inches and 0.095 inches |
| Thready (| Qty Per Inch (tpi): |
| 40 | |
| Material: | |
| Steel com | p 302 or steel comp 303 or steel comp 304 or steel comp 305 |
| Material S | Specification: |
| 66 federal | standard all material responses |
| Surface T | Treatment: |
| Passivate | |
| Thread Se | eries Designator: |
| Unc | |
| Shelf Life | |
| N/a | |
| Unit Of M | leasure: |
| | |
| Demilitari | ization: |
| No | |
| Fiig: | |
| A003b0 | |