NSN 5305-01-009-2253

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-009-2253 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.500 inches and 0.531 inches **Fastener Length:** Between 0.500 inches and 0.531 inches **Head Style:** Pan **Head Diameter:** Between 0.473 inches and 0.492 inches **Head Height:** Between 0.162 inches and 0.175 inches **Locking Feature:** Patch threads or pellet threads or strip threads **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.250 inches Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 160000 pounds per square inch **Surface Finish:** 32.0 microinches threads Material: Plastic polyamide locking feature **Material Specification:** Nas 498 military specification single material response **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Qq-p-416, type 2, cl 2 federal specification all treatment responses **Thread Series Designator:** Unf **Specification Data:** 80205-nas1190 professional/industrial association standard Shelf Life: N/a

Unit Of Measure:

NSN 5305-01-009-2253

Socket Head Cap Screw - Page 2 of 2



em			

No

Fiig:

A003b0

Mil-std (military Standard):

spec.