NSN 5305-01-009-5122



Shoulder Screw - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5305-01-009-5122 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.295 inches and 0.300 inches **Fastener Length:** Between 0.620 inches and 0.635 inches **Head Style:** Flat chamfer **Head Diameter:** 0.380 inches **Head Height:** Between 0.060 inches and 0.070 inches **Shoulder Diameter:** 0.249 inches first shoulder **Shoulder Length:** 0.080 inches first shoulder **Internal Drive Style:** Slot **Thread Diameter:** 0.164 inches Thready Qty Per Inch (tpi): 32 Hardness Rating: 42.0 rockwell c **Shoulder Shape:** Round first shoulder **Special Features:** 3rd shoulder 0.249 in. Diameter by 0.187 in. Lg Material: Steel **Material Specification:** Ams 5643 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:**

Unc

Shelf Life:

N/a

NSN 5305-01-009-5122

Shoulder Screw - Page 2 of 2



ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

No

Fiig:

A003b0