

View Online at <https://aerobasegroup.com/nsn/5305-01-009-6664>

Thread Class:

2a

Thread Direction:

Right-hand

Thread Length:

Between 0.262 inches and 0.312 inches

Fastener Length:

0.312 inches

Head Style:

Fillister

Head Diameter:

Between 0.166 inches and 0.183 inches

Head Height:

Between 0.069 inches and 0.079 inches

Internal Drive Style:

Slot

Thread Diameter:

0.112 inches

Thready Qty Per Inch (tpi):

40

Screw Material:

Steel comp 301 or steel comp 302 or steel comp 302b or steel comp 303 or steel comp 303 plus x or steel comp 303se or steel comp 304 or steel comp 304l or steel comp 305 or steel comp 308 or steel comp 309 or steel comp 309s or steel comp 310 or steel comp 310s or steel comp 314 or steel comp 316 or steel comp 316l or steel comp 317 or steel comp 321 or steel comp 323 or steel comp 324 or steel comp 347 or steel comp 348 or steel comp 384 or steel comp 385

Screw Surface Treatment:

Passivate

Screw Surface Treatment Specification:

171, finish no. 5.4.1 military standard single treatment response

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A500d0