NSN 5305-01-009-6676



View Online at https://aerobasegroup.com/nsn/5305-01-009-6676
Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 1.127 inches and 1.250 inches
Fastener Length:
Between 1.210 inches and 1.250 inches
Head Style:
Flat chamfer
Head Diameter:
Between 0.550 inches and 0.562 inches
Head Height:
Between 0.368 inches and 0.375 inches
Hole Diameter:
0.064 inches
Internal Drive Style:
Hexagon
Thread Diameter:
0.375 inches
Width Across Flats:
Between 0.313 inches and 0.316 inches
Hole Quantity:
6
Hole Type:
Drilled
Thready Qty Per Inch (tpi):
24
Min. Tensile Strength (psi):
170000 pounds per square inch
Hardness Rating:
38.0 rockwell c and 45.0 rockwell c
Minimum Yield Strength:
150000 pounds per square inch
Hole Configuration Style:
Round longitudinal hole

Material:

Steel

Surface Treatment:

Cadmium and chromate

Surface Treatment Specification:

Qq-p-416, type 2, class 2 federal specification all treatment responses

NSN 5305-01-009-6676

Socket Head Cap Screw - Page 2 of 2



Thread Series Designator:	
Unrf	
Specification Data:	
80205-nas1351 professional/industrial association standard	
Shelf Life:	
N/a	
Unit Of Measure:	
Demilitarization:	
No	
Fiig:	

A003b0