NSN 5305-01-009-7124

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-009-7124
Thread Class:
2a
Thread Direction:
Right-hand
Thread Length:
Between 0.407 inches and 0.500 inches
Fastener Length:
Between 0.469 inches and 0.500 inches
Head Style:
Pan
Head Diameter:
Between 0.256 inches and 0.270 inches
Head Height:
Between 0.087 inches and 0.097 inches
Internal Drive Style:
Cross recess type 1
Thread Diameter:
0.138 inches
Thready Qty Per Inch (tpi):
32
Min. Tensile Strength (psi):
80000 pounds per square inch
Screw Material:
Stainless steel
Screw Material Specification:
Qq-s-763, 300 series federal specification single material response or 66, 300 series federal standard single material response or comp
16-18 or 18-8 assn standard single material response
Screw Surface Treatment:
Passivate
Screw Surface Treatment Specification:
Qq-p-35 federal specification single treatment response
Special Test Features:
Special quality control testing
Test Data Document:
81349-mil-p-23199 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Thread Series Designator:
Unc
Specification Or Standard:
3 type and 9c style

Shelf Life:

Departure From Cited Designator:

As mod by packaging which must conform to ships parts control center special quality control provisions

NSN 5305-01-009-7124

Machine Screw - Page 2 of 2



	• •				
In	18	<i>(</i>)+	МЛО	201	ure:

--

Demilitarization:

No

Fiig:

A500d0