

View Online at <https://aerobasegroup.com/nsn/5305-01-009-7138>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.526 inches and 0.562 inches

**Fastener Length:**

0.562 inches

**Head Style:**

Fillister

**Head Diameter:**

Between 0.124 inches and 0.140 inches

**Head Height:**

Between 0.053 inches and 0.062 inches

**Internal Drive Style:**

Slot

**Thread Diameter:**

0.086 inches

**Thready Qty Per Inch (tpi):**

56

**Screw Material:**

Steel comp 301 or steel comp 4320h or steel comp 302b or steel comp 303 or steel comp 303se or steel comp 303 plus x or steel comp 304 or steel comp 304l or steel comp 305 or steel comp 308 or steel comp 309 or steel comp 309s or steel comp 310 or steel comp 310s or steel comp 314 or steel comp 321 or steel comp 323 or steel comp 324 or steel comp 347 or steel comp 348 or steel comp 384 or steel comp 385 or steel comp 634

**Screw Surface Treatment:**

Passivate

**Screw Surface Treatment Specification:**

171, finish no. 5.4.1 military standard single treatment response

**Thread Series Designator:**

Unc

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A500d0