

View Online at <https://aerobasegroup.com/nsn/5305-01-009-9764>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Thread Length:**

0.312 inches

**Fastener Length:**

Between 0.282 inches and 0.312 inches

**Head Style:**

Flat countersunk

**Head Diameter:**

Between 0.156 inches and 0.172 inches

**Locking Feature:**

Strip threads

**Internal Drive Style:**

Cross recess type 1

**Thread Diameter:**

0.086 inches

**Thready Qty Per Inch (tpi):**

56

**Countersink Angle:**

100.0 degrees

**Material:**

Steel comp 302 or steel comp 303 or steel comp 321 or steel comp 347

**Material Specification:**

Mil-s-7720 military specification 1st material response or mil-s-7720, comp 303s military specification 2nd material response or qq-s-763, class 8, type a federal specification 3rd material response or qq-s-763, class 8, type a federal specification 4th material response

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response

**Thread Series Designator:**

Unc

**Specification Data:**

80205-nas662 professional/industrial association standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0

**Mil-std (military Standard):**

Mil-s-7720 spec.