

View Online at <https://aerobasegroup.com/nsn/5305-01-009-9764>

Thread Class:

2a

Thread Direction:

Right-hand

Thread Length:

0.312 inches

Fastener Length:

Between 0.282 inches and 0.312 inches

Head Style:

Flat countersunk

Head Diameter:

Between 0.156 inches and 0.172 inches

Locking Feature:

Strip threads

Internal Drive Style:

Cross recess type 1

Thread Diameter:

0.086 inches

Thready Qty Per Inch (tpi):

56

Countersink Angle:

100.0 degrees

Material:

Steel comp 302 or steel comp 303 or steel comp 321 or steel comp 347

Material Specification:

Mil-s-7720 military specification 1st material response or mil-s-7720, comp 303s military specification 2nd material response or qq-s-763, class 8, type a federal specification 3rd material response or qq-s-763, class 8, type a federal specification 4th material response

Surface Treatment:

Passivate

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

Thread Series Designator:

Unc

Specification Data:

80205-nas662 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-7720 spec.