NSN 5305-01-010-1569

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-010-1569 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.125 inches and 0.225 inches **Fastener Length:** Between 0.562 inches and 0.672 inches **Head Style:** Pan no. 2 **Head Diameter:** Between 0.256 inches and 0.270 inches **Head Height:** Between 0.087 inches and 0.097 inches **First Diameter From Head:** Between 0.096 inches and 0.099 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.437 inches and 0.447 inches **Internal Drive Style:** Cross recess type 1 **End Application:** An/alq-13 (v) **Thread Diameter:** 0.138 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 130000 pounds per square inch **Hardness Rating:** 39.0 rockwell c and 43.0 rockwell c **Externally Relieved Body Diameter Quantity:** Material: Steel comp 410 **Material Specification:** Qq-s-763, cond h federal specification single material response **Surface Treatment: Passivate Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response

Thread Series Designator:

Unc

NSN 5305-01-010-1569

Externally Relieved Body Screw - Page 2 of 2



She	lf	Life:	
Oile	••	LIIV.	

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0