

View Online at <https://aerobasegroup.com/nsn/5305-01-010-2301>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.113 inches and 0.154 inches

**Fastener Length:**

0.187 inches

**Head Style:**

Flat countersunk

**Head Diameter:**

Between 0.130 inches and 0.146 inches

**Internal Drive Style:**

Slot

**Thread Diameter:**

0.073 inches

**Thready Qty Per Inch (tpi):**

64

**Countersink Angle:**

82.0 degrees

**Screw Material:**

Steel comp 301 or steel comp 302 or steel comp 302b or steel comp 303 or steel comp 303 plus x or steel comp 303se or steel comp 304 or steel comp 304l or steel comp 305 or steel comp 308 or steel comp 309 or steel comp 309s or steel comp 310 or steel comp 310s or steel comp 314 or steel comp 316 or steel comp 316l or steel comp 317 or steel comp 321 or steel comp 323 or steel comp 324 or steel comp 347 or steel comp 348 or steel comp 384 or steel comp 385

**Screw Surface Treatment:**

Passivate

**Screw Surface Treatment Specification:**

171, finish no. 5.4.1 military standard single treatment response

**Thread Series Designator:**

Unc

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A500d0