## NSN 5305-01-010-2337

Thumbscrew - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-010-2337 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.240 inches and 0.300 inches **Fastener Length:** Between 0.730 inches and 0.770 inches **Head Style:** Thumb no. 3 **Head Height:** Between 0.750 inches and 0.780 inches Width Between Flats: Between 0.667 inches and 0.697 inches **First Diameter From Head:** Between 0.245 inches and 0.255 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.470 inches and 0.490 inches **Point Style:** Flat **Thread Diameter:** 0.312 inches Thready Qty Per Inch (tpi): 24 Material: Steel comp 302 **Material Specification:** Mil-s-7720 military specification single material response **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35, type 2 federal specification single treatment response **Thread Series Designator:** Unf Shelf Life: N/a **Unit Of Measure:** 

**Demilitarization:** No

Fiig:

A003b0

## NSN 5305-01-010-2337

Thumbscrew - Page 2 of 2



Mil-std (military Standard):

Mil-s-7720 spec.