NSN 5305-01-010-2338

Thumbscrew - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-010-2338 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.620 inches and 0.780 inches **Fastener Length:** Between 0.720 inches and 0.780 inches **Head Style:** Thumb no. 3 **Head Height:** 0.625 inches Width Between Flats: 0.535 inches **Point Style:** Flat **Thread Diameter:** 0.250 inches Thready Qty Per Inch (tpi): 20 Material: Steel **Surface Treatment:** Cadmium and chromate **Special Test Features:** Special quality control testing **Surface Treatment Specification:** Qq-p-416, ty2 cl3 federal specification single treatment response or mil-c-81562 ty2 cl3 military specification single treatment response **Test Data Document:** 81349-mil-p-23199 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). **Thread Series Designator:** Unc **Departure From Cited Designator:** As modified by material which must conform to ships parts control center special quality controll provisions Shelf Life: N/a **Unit Of Measure:**

Fiig: A003b0

No

Demilitarization:

NSN 5305-01-010-2338

Thumbscrew - Page 2 of 2



Mil-std (military Standard):

Mil-c-81562 spec.