## NSN 5305-01-010-2339



Thumbscrew - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5305-01-010-2339 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.270 inches and 0.350 inches **Fastener Length:** Between 0.730 inches and 0.770 inches **Head Style:** Thumb no. 3 **Head Height:** Between 0.453 inches and 0.483 inches Width Between Flats: Between 0.395 inches and 0.425 inches **First Diameter From Head:** Between 0.120 inches and 0.130 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.420 inches and 0.460 inches **Point Style:** Flat **Thread Diameter:** 0.190 inches Thready Qty Per Inch (tpi): 32 Material: Steel comp 302 **Material Specification:** Mil-s-7720 military specification single material response **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unf Shelf Life: N/a **Unit Of Measure: Demilitarization:** 

No Fiig:

A003b0

## NSN 5305-01-010-2339

Thumbscrew - Page 2 of 2



Mil-std (military Standard):

Mil-s-7720 spec.