## NSN 5305-01-010-2348

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-010-2348 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 1.110 inches and 1.250 inches **Fastener Length:** Between 1.210 inches and 1.250 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.480 inches and 0.531 inches **Internal Drive Style:** Hexagon **Thread Diameter:** 0.250 inches Width Across Flats: 0.156 inches Thready Qty Per Inch (tpi): 20 Min. Tensile Strength (psi): 80000 pounds per square inch **Hardness Rating:** 80.0 rockwell b Minimum Yield Strength: 30000 pounds per square inch **Countersink Angle:** 82.0 degrees Material: Steel comp 302 or steel comp 303 or steel comp 304 or steel comp 305 or steel comp 316 or steel comp 384 **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unc **Specification Or Standard:** 4 type Shelf Life: N/a

**Unit Of Measure:** 

## NSN 5305-01-010-2348

Socket Head Cap Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0