

View Online at <https://aerobasegroup.com/nsn/5305-01-010-2357>

Thread Class:

2a

Thread Direction:

Right-hand

Thread Length:

Between 1.750 inches and 2.000 inches

Fastener Length:

Between 2.156 inches and 2.250 inches

Head Style:

Hexagon

Head Height:

Between 0.455 inches and 0.483 inches

Width Between Flats:

Between 1.100 inches and 1.125 inches

Hole Diameter:

0.094 inches

Thread Diameter:

0.750 inches

Hole Quantity:

1

Hole Type:

Drilled

Thready Qty Per Inch (tpi):

10

Min. Tensile Strength (psi):

70000 pounds per square inch

Hardness Rating:

235.0 brinell standard

Minimum Yield Strength:

40000 pounds per square inch

Hole Configuration Style:

Hexagon flats

Surface Finish:

63.0 microinches threads

Material:

Steel comp 403 or steel comp 405 or steel comp 410 or steel comp 414 or steel comp 416 or steel comp 416se or steel comp 420 or steel comp 430 or steel comp 431 or steel comp 440a or steel comp 440b or steel comp 440c or steel comp 430f

Surface Treatment:

Passivate

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

Thread Series Designator:

Unc

Specification Or Standard:

2 type and 10p style

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0