## NSN 5305-01-010-3324

**Thread Class:** 

3a

Socket Head Cap Screw - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5305-01-010-3324



## **Thread Direction: Right-hand Thread Length:** Between 0.359 inches and 0.453 inches Fastener Length: Between 0.719 inches and 0.781 inches **Head Style:** Round extended washer **Head Diameter:** 0.312 inches **Head Height:** Between 0.082 inches and 0.092 inches **Extended Washer Diameter:** 0.375 inches **Extended Washer Thickness:** Between 0.023 inches and 0.028 inches Locking Feature: Patch threads or pellet threads **Internal Drive Style:** Slot **Thread Diameter:** 0.164 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 125000 pounds per square inch Material: Steel comp 4037 fastener or steel comp 8630 fastener **Surface Treatment:** Cadmium fastener and zinc fastener Surface Treatment Specification: Astm b633 assn standard single treatment response fastener **Thread Series Designator:** Unc Shelf Life: N/a Unit Of Measure: ---

**Demilitarization:** 

No

## NSN 5305-01-010-3324

Socket Head Cap Screw - Page 2 of 2

Fiig: A003b0

