NSN 5305-01-010-9923

Thread Class:

Right-hand

Thread Direction:

2a

Assembled Washer Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-010-9923

ragin hand
Thread Length:
Between 0.610 inches and 0.641 inches
Fastener Length:
Between 0.719 inches and 0.750 inches
Head Style:
Pan
Head Diameter:
Between 0.407 inches and 0.425 inches
Head Height:
Between 0.139 inches and 0.151 inches
Washer Quantity:
2
Internal Drive Style:
Cross recess type 1
Thread Diameter:
0.216 inches
Thready Qty Per Inch (tpi):
24
Secondary Washer Relationship To Primary Washer:
Not identical
Secondary Washer Style:
Flat
Primary Washer Outside Diameter:
Between 0.414 inches and 0.429 inches
Secondary Washer Outside Diameter:
Between 0.485 inches and 0.515 inches
Primary Washer Style:
Split helical ring
Primary Washer Material Thickness:
0.063 inches
Secondary Washer Material Thickness:
0.046 inches
Product Name:
Navy special project
Material:
Steel comp 305 or steel comp 410
Surface Treatment:
Passivate

NSN 5305-01-010-9923

Assembled Washer Screw - Page 2 of 2



Thread Series Designator:
Unc
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A003b0