Assembled Washer Screw - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5305-01-010-9923



Thread Class: 2a **Thread Direction: Right-hand Thread Length:** Between 0.610 inches and 0.641 inches Fastener Length: Between 0.719 inches and 0.750 inches **Head Style:** Pan **Head Diameter:** Between 0.407 inches and 0.425 inches **Head Height:** Between 0.139 inches and 0.151 inches Washer Quantity: 2 **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.216 inches Thready Qty Per Inch (tpi): 24 Secondary Washer Relationship To Primary Washer: Not identical Secondary Washer Style: Flat Primary Washer Outside Diameter: Between 0.414 inches and 0.429 inches Secondary Washer Outside Diameter: Between 0.485 inches and 0.515 inches **Primary Washer Style:** Split helical ring **Primary Washer Material Thickness:** 0.063 inches Secondary Washer Material Thickness: 0.046 inches **Product Name:** Navy special project Material: Steel comp 305 or steel comp 410 **Surface Treatment:** Passivate

NSN 5305-01-010-9923

Assembled Washer Screw - Page 2 of 2



Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A003b0