## NSN 5305-01-010-9926

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-010-9926 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.750 inches **Fastener Length:** Between 0.970 inches and 1.000 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.176 inches and 0.183 inches **Head Height:** Between 0.108 inches and 0.112 inches **Internal Drive Style:** Hexagon **Thread Diameter:** 0.112 inches Width Across Flats: Between 0.094 inches and 0.095 inches Thready Qty Per Inch (tpi): 40 Min. Tensile Strength (psi): 180000 pounds per square inch Hardness Rating: 38.0 rockwell c and 45.0 rockwell c Minimum Yield Strength: 155000 pounds per square inch Material: Steel **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Qq-p-416, type 2, class 2 federal specification all treatment responses **Thread Series Designator:** Unrc **Specification Data:** 80205-nas1352 professional/industrial association standard Shelf Life: N/a

--

**Unit Of Measure:** 

## NSN 5305-01-010-9926

Socket Head Cap Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0