Socket Head Cap Screw - Page 1 of 2





View Online at https://aerobasegroup.com/nsn/5305-01-010-9940

## **Thread Class:** 3a **Thread Direction: Right-hand Thread Length:** Between 0.667 inches and 0.750 inches Fastener Length: Between 0.720 inches and 0.750 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.303 inches and 0.312 inches **Head Height:** Between 0.185 inches and 0.190 inches **Internal Drive Style:** Hexagon **Thread Diameter:** 0.190 inches Width Across Flats: Between 0.156 inches and 0.159 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 80000 pounds per square inch Hardness Rating: 80.0 rockwell b **Minimum Yield Strength:** 30000 pounds per square inch Material: **Surface Treatment:** Passivate Surface Treatment Specification: **Thread Series Designator:** Unc **Specification Data:** Shelf Life:

Steel comp 302 or steel comp 304 or steel comp 305 or steel comp 316 or steel comp 384 or steel comp xm-7

Qq-p-35 federal specification single treatment response

80205-nas1352 professional/industrial association standard

N/a

## Unit Of Measure:

---

## NSN 5305-01-010-9940

Socket Head Cap Screw - Page 2 of 2

Demilitarization:

No

Fiig:

A003b0

