

View Online at <https://aerobasegroup.com/nsn/5305-01-010-9943>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.306 inches and 0.355 inches

**Fastener Length:**

Between 3.978 inches and 3.996 inches

**Head Style:**

Crowned hexagon

**Head Height:**

Between 0.157 inches and 0.172 inches

**Width Between Flats:**

Between 0.492 inches and 0.502 inches

**Locking Feature:**

Detent ball grip

**Grip Diameter:**

Between 0.3112 inches and 0.3117 inches

**Shank Unthreaded Hole Diameter:**

0.076 inches first hole and 0.086 inches first hole

**Internal Drive Style:**

Slot

**Thread Diameter:**

0.312 inches

**Grip Length:**

Between 3.500 inches and 3.516 inches

**Thready Qty Per Inch (tpi):**

24

**Distance From Head Largest Bearing Surface To Shank Hole Center:**

3.875 inches first hole and 3.891 inches first hole

**Surface Finish:**

32.0 microinches grip

**Special Features:**

Retaining element in shank

**Material:**

Steel comp 630

**Material Specification:**

Ams 5643 assn standard single material response

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0