

View Online at <https://aerobasegroup.com/nsn/5305-01-011-3933>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

0.400 inches

**Fastener Length:**

Between 1.515 inches and 1.535 inches

**Head Style:**

Flat countersunk

**Head Diameter:**

Between 0.752 inches and 0.762 inches

**Grip Diameter:**

Between 0.3735 inches and 0.3745 inches

**Shank Unthreaded Hole Diameter:**

0.106 inches first hole and 0.111 inches first hole

**Internal Drive Style:**

High-torque

**Thread Diameter:**

0.375 inches

**Grip Length:**

Between 1.115 inches and 1.135 inches

**Thready Qty Per Inch (tpi):**

24

**Min. Tensile Strength (psi):**

17000 pounds per square inch

**Countersink Angle:**

Between 99.0 degrees and 101.0 degrees

**Distance From Head Largest Bearing Surface To Shank Hole Center:**

0.115 inches first hole and 0.125 inches first hole

**Material:**

Steel

**Material Specification:**

23-105 fscm 76301 mfr ref single material response

**Surface Treatment:**

Cadmium

**Surface Treatment Specification:**

Mac ps13145, mcdonnell douglas corporation mfr ref single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0