NSN 5305-01-011-6099



Machine Screw - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5305-01-011-6099 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.352 inches and 0.466 inches **Fastener Length:** Between 0.594 inches and 0.625 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.686 inches and 0.762 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.375 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 125000 pounds per square inch Hardness Rating: Between 26.0 rockwell c and 32.0 rockwell c **Countersink Angle:** 100.0 degrees **Screw Material:** Steel comp 4037 or steel comp 8630 **Screw Material Specification:** Ams 6300 assn standard 1st material response or mil-s-6050 military specification 2nd material response **Screw Surface Treatment Specification:** Qq-p-416, type 2, cl 2 federal specification single treatment response **Thread Series Designator:** Unjf **Specification Data:** 80205-nas514 professional/industrial association standard

N/a Unit Of Measure:

Shelf Life:

Demilitarization:

No

Fiig:

A500d0

NSN 5305-01-011-6099

Machine Screw - Page 2 of 2



Mil-std (military Standard):

Mil-s-6050 spec.