## NSN 5305-01-011-6510

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-011-6510 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.379 inches and 0.410 inches **Fastener Length:** Between 0.719 inches and 0.750 inches **Head Style:** Fillister **Head Diameter:** Between 0.250 inches and 0.270 inches **Head Height:** Between 0.106 inches and 0.113 inches **Hole Diameter:** 0.046 inches First Diameter From Head: Between 0.115 inches and 0.125 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.340 inches **Internal Drive Style:** Slot **Thread Diameter:** 0.164 inches **Hole Quantity: Hole Type:** Drilled Thready Qty Per Inch (tpi): 32 **Hole Configuration Style: Externally Relieved Body Diameter Quantity:** Material: Steel comp 302 or steel comp 303 or steel comp 304 or steel comp 305 or steel comp 316 **Material Specification:** 66 federal standard all material responses **Surface Treatment: Passivate** 

**Surface Treatment Specification:** 

Qq-p-35 federal specification single treatment response

## NSN 5305-01-011-6510

Externally Relieved Body Screw - Page 2 of 2



Inread Series Designator
Unc
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A003b0