NSN 5305-01-012-8928

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-012-8928
Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.277 inches and 0.328 inches
Fastener Length:
Between 1.418 inches and 1.438 inches
Head Style:
Crowned hexagon
Head Height:
Between 0.126 inches and 0.141 inches
Width Between Flats:
Between 0.430 inches and 0.439 inches
Grip Diameter:
Between 0.2487 inches and 0.2492 inches
Shank Unthreaded Hole Diameter:
0.076 inches first hole and 0.086 inches first hole
Internal Drive Style:
Slot
Thread Diameter:
0.250 inches
Grip Length:
Between 1.000 inches and 1.016 inches
Thready Qty Per Inch (tpi):
28
Distance From Head Largest Bearing Surface To Shank Hole Center:
1.323 inches first hole and 1.343 inches first hole
Surface Finish:
32.0 microinches grip
Special Features:
Retaining element in shank
Material:
Steel comp xm-13
Material Specification:
Ams 5629 assn standard single material response
Surface Treatment:
Passivate
Surface Treatment Specification:
Qq-p-35 federal specification single treatment response
Thread Series Designator:
Unjf

Unjf

NSN 5305-01-012-8928

Close Tolerance Screw - Page 2 of 2



	Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0