NSN 5305-01-013-3182

Setscrew - Page 1 of 2

Between 0.250 inches and 0.255 inches

Thread Class:

Right-hand

Thread Length:

Thread Direction:

Fastener Length:

За



View Online at https://aerobasegroup.com/nsn/5305-01-013-3182

| 0.312 inches |
|---|
| Head Style: |
| Flat chamfer |
| Head Diameter: |
| Between 0.085 inches and 0.090 inches |
| Head Height: |
| Between 0.070 inches and 0.073 inches |
| Spline Minor Diameter: |
| Between 0.063 inches and 0.064 inches |
| Spline Major Diameter: |
| Between 0.073 inches and 0.074 inches |
| Spline Width: |
| Between 0.015 inches and 0.016 inches |
| Point Length: |
| 0.057 inches |
| Point Diameter: |
| Between 0.048 inches and 0.050 inches |
| Point Style: |
| Ball |
| Internal Drive Style: |
| Six spline |
| Thread Diameter: |
| 0.073 inches |
| Thready Qty Per Inch (tpi): |
| 72 |
| Material: |
| Steel comp 303 |
| Material Specification: |
| Astm a582 assn standard single material response |
| Surface Treatment: |
| Passivate |
| Surface Treatment Specification: |
| Qq-p-35 federal specification single treatment response |
| Thread Series Designator: |
| Unf |
| |

NSN 5305-01-013-3182

Setscrew - Page 2 of 2



| C | ha | Ιf | 1 | ife | |
|---|-----|----|---|-------|--|
| • | ııe | | _ | .II C | |

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0