## NSN 5305-01-013-9599



Close Tolerance Screw - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5305-01-013-9599 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.466 inches **Fastener Length:** Between 2.012 inches and 2.059 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.880 inches and 0.890 inches **Grip Diameter:** Between 0.4360 inches and 0.4370 inches **Shank Unthreaded Hole Diameter:** 0.106 inches first hole and 0.111 inches first hole **Internal Drive Style:** High-torque **Thread Diameter:** 0.438 inches **Grip Length:** Between 1.552 inches and 1.572 inches Thready Qty Per Inch (tpi): 20 **Countersink Angle:** 100.0 degrees Distance From Head Largest Bearing Surface To Shank Hole Center: 1.884 inches first hole and 1.941 inches first hole Material: Steel **Surface Treatment:** Cadmium **Surface Treatment Specification:** Mac ps13145, fscm 76301 mfr ref single treatment response **Thread Series Designator:** Unjf **Specification Data:** 76301-st3-562 professional/industrial association standard Shelf Life: N/a

**Unit Of Measure:** 

## NSN 5305-01-013-9599

Close Tolerance Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0