

View Online at <https://aerobasegroup.com/nsn/5305-01-013-9600>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.466 inches

Fastener Length:

Between 2.262 inches and 2.309 inches

Head Style:

Flat countersunk

Head Diameter:

Between 0.880 inches and 0.890 inches

Grip Diameter:

Between 0.4360 inches and 0.4370 inches

Shank Unthreaded Hole Diameter:

0.106 inches first hole and 0.111 inches first hole

Internal Drive Style:

High-torque

Thread Diameter:

0.438 inches

Grip Length:

Between 1.802 inches and 1.822 inches

Thready Qty Per Inch (tpi):

20

Countersink Angle:

100.0 degrees

Distance From Head Largest Bearing Surface To Shank Hole Center:

2.134 inches first hole and 2.191 inches first hole

Special Features:

Heat treated and plated

Material:

Steel

Surface Treatment:

Cadmium

Surface Treatment Specification:

Mac ps13145, fscm 76301 mfr ref single treatment response

Thread Series Designator:

Unjf

Specification Data:

76301-st3-562 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0