# NSN 5305-01-014-1172

Machine Screw - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5305-01-014-1172



**Thread Class:** 

3a

**Thread Direction:** 

**Right-hand** 

Thread Length:

Between 0.375 inches and 0.438 inches

#### Fastener Length:

Between 0.531 inches and 0.594 inches

Head Style:

Round extended washer

Head Diameter:

0.375 inches

Head Height:

Between 0.089 inches and 0.099 inches

#### **Extended Washer Diameter:**

0.437 inches

#### **Extended Washer Thickness:**

Between 0.025 inches and 0.030 inches

#### Internal Drive Style:

Cross recess type 1

## Thread Diameter:

0.190 inches

### Thready Qty Per Inch (tpi):

32

# Min. Tensile Strength (psi):

125000 pounds per square inch

### Screw Material:

Steel comp 8630 or steel comp 4037

# Screw Material Specification:

Mil-s-6050 military specification 1st material response or ams 6300 assn standard 2nd material response

# Screw Surface Treatment:

Cadmium and chromate

# Screw Surface Treatment Specification:

Qq-p-416, type 2, cl 3 federal specification single treatment response

# Thread Series Designator:

Unf

Shelf Life:

N/a

## Unit Of Measure:

--

#### Demilitarization:

No

# NSN 5305-01-014-1172

Machine Screw - Page 2 of 2

**Fiig:** A500d0

Mil-std (military Standard):

Mil-s-6050 spec.

