## NSN 5305-01-014-2203

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-014-2203

view Offilite at https://defobasegroup.com/hsh/5505-01-014-2205
Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.553 inches and 0.603 inches
Fastener Length:
Between 1.189 inches and 1.219 inches
Head Style:
Flat countersunk
Head Diameter:
Between 0.703 inches and 0.762 inches
Internal Drive Style:
High-torque
Thread Diameter:
0.375 inches
Thready Qty Per Inch (tpi):
24
Min. Tensile Strength (psi):
160000 pounds per square inch
Hardness Rating:
Between 36.0 rockwell c and 40.0 rockwell c
Countersink Angle:
Between 99.0 degrees and 101.0 degrees
Product Name:
Navy special project
Screw Material:
Iron alloy 660
Screw Material Specification:
Ams 5731 assn standard single material response or ams 5737 assn standard single material response
Screw Surface Treatment:
Passivate
Screw Surface Treatment Specification:
Qq-p-35 federal specification single treatment response
Thread Series Designator:
Unjf
Specification Data:
80205-nas1221 professional/industrial association standard
Shelf Life:
N/a
Unit Of Measure:

--

## NSN 5305-01-014-2203

Machine Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A500d0