NSN 5305-01-014-2205

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-014-2205 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.375 inches and 0.437 inches **Fastener Length:** Between 0.719 inches and 0.781 inches **Head Style:** Round extended washer **Head Diameter:** 0.375 inches **Head Height:** Between 0.089 inches and 0.099 inches **Extended Washer Diameter:** 0.437 inches **Extended Washer Thickness:** Between 0.025 inches and 0.030 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.190 inches Thready Qty Per Inch (tpi): Min. Tensile Strength (psi): 125000 pounds per square inch **Screw Material:** Steel comp 8630 or steel comp 4037 **Screw Material Specification:** Mil-s-6050 military specification 1st material response or ams 6300 assn standard 2nd material response **Screw Surface Treatment:** Cadmium and chromate **Screw Surface Treatment Specification:** Qq-p-416, type 2, cl 3 federal specification single treatment response **Thread Series Designator:** Unf Shelf Life: N/a

Demilitarization: No

Unit Of Measure:

NSN 5305-01-014-2205

Machine Screw - Page 2 of 2



Fiig:

A500d0

Mil-std (military Standard):

Mil-s-6050 spec.