NSN 5305-01-014-4256

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-014-4256

Inread Direction: 3a Thread Direction: Right-hand Thread Length: Between 0.331 inches and 0.431 inches Fastener Length: Between 0.628 inches and 0.658 inches Head Style: Fillister countersunk Head Diameter: Between 0.2966 inches and 0.3016 inches Head Height: 0.013 inches Grip Diameter: Between 0.1885 inches and 0.1895 inches Internal Drive Style: High-torque End Application: Aircraft, thunderbolt ii, a-10; aircraft, eagle f-15 Thread Diameter: 0.190 inches Grip Length: Between 0.227 inches and 0.247 inches Thread Qity Per Inch (tpi): 32 Countersink Angle: 100.0 degrees Surformiches threads Material: Stel comp xm-13 Material: Stel comp xm-13 Material: Unit of Measure: Interial Specification: Interial Specification: Interial Specificatine:	
Thread Direction: Right-hand Thread Length: Between 0.381 inches and 0.431 inches Fastener Length: Between 0.628 inches and 0.658 inches Head Style: Fillister countersunk Head Diameter: Between 0.2966 inches and 0.3016 inches Head Height: 0.013 inches Grip Diameter: Between 0.1885 inches and 0.1895 inches Internal Drive Style: High-torque Aircraft, thunderbott ii, a-10; aircraft, eagle f-15 Thread Diameter: 0.190 inches Grip Length: Between 0.227 inches and 0.247 inches Thready Qty Per Inch (tpl): 32 Countersink Angle: 100.0 degrees Surface Finish: 32.0 microinches threads Material Steel comp xm-13 Material Specification: Airs Steel assi standard single material response Thread Stries Designator: Unif Sheff Life: Na Unif Sheff Life: Na </th <th>Thread Class:</th>	Thread Class:
Right-hand Thread Length: Between 0.831 inches and 0.431 inches Fastener Length: Between 0.628 inches and 0.658 inches Head Style: Fillister countersunk Head Diameter: Between 0.2966 inches and 0.3016 inches Head Height: 0.013 inches Grip Diameter: Between 0.1885 inches and 0.1895 inches Internal Drive Style: High-torque Antoraft, thunderbolt ii, a-10; aircraft, eagle f-15 Thread Diameter: 0.190 inches Grip Langeth: Between 0.227 inches and 0.247 inches Thready Qty Per Inch (tpi): 32 Countersink Angle: 10.0.0 degrees Surface Finish: 32.0 microinches threads Material Surface Sustantard single material response Thread Series Designator: Unjr Shelf Life: N/a Dit of Measure: Image: Between 0.227 inches and 0.247 inches Between 0.227 inches and 0.247 inches Between 0.227 inches and 0.2	
Tread Length: Between 0.381 inches and 0.431 inches Fastener Length: Between 0.628 inches and 0.658 inches Head Style: Fillister countersunk Head Diameter: Between 0.2966 inches and 0.3016 inches Head Height: 0.013 inches Grip Diameter: Between 0.1885 inches and 0.1895 inches Internal Drive Style: High-torque End Application: Aircraft, thunderbolt ii, a-10; aircraft, eagle f-15 Thread Diameter: 0.190 inches Grip Length: Between 0.227 inches and 0.247 inches Thread Qty Per Inch (tpi): 32 Countersink Angle: 100.0 degrees Surface Finish: 32.0 microinches threads Material: Steel comp xm-13 Material Specification: Ams 5629 assn standard single material response Thread Series Designator: Unjr Shelf Life: N/a Enter Life: N/a	
Between 0.628 inches and 0.658 inches Fastener Length: Between 0.628 inches and 0.658 inches Head Style: Fillister countersunk Head Diameter: Between 0.2966 inches and 0.3016 inches Head Heigh: 0.013 inches Gotta inches Head Heigh: 0.013 inches Between 0.1885 inches and 0.1895 inches Internal Drive Style: High-torque End Application: Aircraft, hunderbolt ii, a-10; aircraft, eagle f-15 Thread Diameter: 0.190 inches Grip Length: Between 0.227 inches and 0.247 inches Thready Qty Per Inch (tpi): 32 Countersink Angle: 10.0 degrees Surface Finish: 32.0 microinches threads Material Steel comp xm-13 Material Specification: Ams 5629 asen standard single material response Thread Seise Designator: Linff Shelf Life: N/a Dint Of Measure: Linff Dint Of Measure:	-
Fastener Length: Between 0.628 inches and 0.658 inches Head Style: Fillister countersunk Head Diameter: Between 0.2966 inches and 0.3016 inches Head Height: 0.013 inches Grip Diameter: Between 0.1885 inches and 0.1895 inches Internal Drive Style: High-torque End Application: Aircraft, thunderbolt ii, a-10; aircraft, eagle f-15 Thread Diameter: 0.190 inches Grip Length: Between 0.227 inches and 0.247 inches Thread Quy Per Inch (tpi): 32 Countersink Angle: 10.0 degrees Surface Finish: 32.0 microinches threads Material Steel comp xm-13 Material Specification: Ams 5629 assn standard single material response Thread Series Designator: Linff N/a Unit Of Measure: Iva Particit Series Designator: High-tories Na Dit Of Measure: Iva	
Between 0.628 inches and 0.658 inches Fillister countersumk Head Diameter: Between 0.2966 inches and 0.3016 inches Head Height: 0.013 inches Grip Diameter: Between 0.1885 inches and 0.1895 inches Internal Drive Style: High-torque End Application: Aircraft, thunderbolt ii, a-10; aircraft, eagle f-15 Thread Diameter: 0.190 inches Between 0.227 inches and 0.247 inches Thready Qty Per Inch (tpi): 32 Countersink Angle: 10.00 degrees Surface Finish: 32.0 microinches threads Material Steel comp xm-13 Material Specification: Inread Series Designator: Unjf Shelf Life: Na Dirt of Measure: Init of Measure: Init of Measure: Init of Measure:	
Head Style: Fillister countersunk Head Diameter: Between 0.2966 inches and 0.3016 inches Head Height: 0.013 inches Grip Diameter: Between 0.1885 inches and 0.1895 inches Internal Drive Style: High-torque End Application: Aircraft, thunderbolt ii, a-10; aircraft, eagle f-15 Thread Diameter: 0.190 inches Grip Length: Between 0.227 inches and 0.247 inches Thready Qty Per Inch (tpi): 32 Countersink Angle: 100.0 degrees Surface Finish: 32.0 microinches threads Material: Steel comp xm-13 Material Specification: Airs 5629 assn standard single material response Thread Series Designator: Unjf Shelf Life: N/a Unit Of Measure: - Demilitarization:	
Filister countersunk Head Diameter: Between 0.2966 inches and 0.3016 inches Head Height: 0.013 inches Grip Diameter: Between 0.1885 inches and 0.1895 inches Internal Drive Style: High-torque End Application: Aircraft, thunderbolt ii, a-10; aircraft, eagle 1-15 Thread Diameter: 0.190 inches Grip Length: Between 0.227 inches and 0.247 inches Thready Qty Per Inch (tpi): 32 Countersink Angle: 10.0 degrees Surface Finish: 32.0 microinches threads Material: Steel comp xm-13 Material Specification: Ams 5629 assn standard single material response Thread Series Designator: Unif Na Unif Cf Measure: Demilitatization:	
Head Diameter: Between 0.2966 inches and 0.3016 inches Head Height: 0.013 inches Grip Diameter: Between 0.1885 inches and 0.1895 inches Internal Drive Style: High-torque End Application: Aircraft, thunderbolt ii, a-10; aircraft, eagle 1-15 Thread Diameter: 0.190 inches Grip Length: Between 0.227 inches and 0.247 inches Thready Qty Per Inch (tpi): 32 Countersink Angle: 100.0 degrees Surface Finish: 32.0 microinches threads Material: Steel comp xm-13 Material Specification: Ams 5629 assn standard single material response Thread Series Designator: Unjf Shelf Life: N/a Unit Of Measure: - Demilitarization:	
Between 0.2966 inches and 0.3016 inches Head Height: 0.013 inches Grip Diameter: Between 0.1885 inches and 0.1895 inches Internal Drive Style: High-torque End Application: Aircraft, thunderbott ii, a-10; aircraft, eagle f-15 Thread Diameter: 0.190 inches Grip Length: Between 0.227 inches and 0.247 inches Thready Qty Per Inch (tpi): 32 Countersink Angle: 100.0 degrees Surface Finish: 32.0 microinches threads Material: Steel comp xm-13 Material Specification: Unif Sheff Life: N/a Unit Of Measure:	
Head Height:0.013 inchesGrip Diameter:Between 0.1885 inches and 0.1895 inchesInternal Drive Style:High-torqueEnd Application:Aircraft, thunderbolt ii, a-10; aircraft, eagle f-15Thread Diameter:0.190 inchesGrip Length:Between 0.227 inches and 0.247 inchesThready Qty Per Inch (tpi):32Contersink Angle:100.0 degreesSurface Finish:32.0 microinches threadsMaterial:Steel comp xm-13Aterial Specification:Ains 5629 assn standard single material responseThread Series Designator:UnifShelf Life:N/aInit of Measure:Demilitarization:	
0.013 inches Grip Diameter: Between 0.1885 inches and 0.1895 inches Internal Drive Style: High-torque End Application: Aircraft, thunderbolt ii, a-10; aircraft, eagle f-15 Thread Diameter: 0.190 inches Grip Length: Between 0.227 inches and 0.247 inches Thready Qty Per Inch (tpi): 32 Countersink Angle: 100.0 degrees Surface Finish: 32.0 microinches threads Material: Steel comp xm-13 Material Specification: Arns 5629 assn standard single material response Thread Stripe Designator: Unif Shaterial: Na Diff Life: N/a Unif Of Measure: N/a Demilitarization:	
Grip Diameter: Between 0.1885 inches and 0.1895 inches Internal Drive Style: High-torque End Application: Aircraft, thunderbolt ii, a-10; aircraft, eagle f-15 Thread Diameter: 0.190 inches Grip Length: Between 0.227 inches and 0.247 inches Thready Qty Per Inch (tpi): 32 Countersink Angle: 100.0 degrees Surface Finish: 32.0 microinches threads Material: Steel comp xm-13 Material Specification: Ams 5629 assn standard single material response Thread Series Designator: Unjf Shell Life: N/a Unif Of Measure: -	-
Between 0.1885 inches and 0.1895 inches Internal Drive Style: High-torque End Application: Aircraft, thunderbolt ii, a-10; aircraft, eagle f-15 Thread Diameter: 0.190 inches Grip Length: Between 0.227 inches and 0.247 inches Thready Qty Per Inch (tpi): 32 Countersink Angle: 100.0 degrees Surface Finish: 32.0 microinches threads Material: Steel comp xm-13 Material Specification: Inse 5629 assn standard single material response Thread Series Designator: Unif Shelf Life: N/a Dint of Measure: Image: Dint of Measure: Image: Image: <t< th=""><th></th></t<>	
Internal Drive Style: High-torque End Application: Aircraft, thunderbolt ii, a-10; aircraft, eagle f-15 Thread Diameter: 0.190 inches Grip Length: Between 0.227 inches and 0.247 inches Thready Qty Per Inch (tpi): 32 Countersink Angle: 100.0 degrees Surface Finish: 32.0 microinches threads Material: Steel comp xm-13 Material Specification: Ams 5629 assn standard single material response Thread Series Designator: Unif Shelf Life: N/a Unif Of Measure: 	-
High-torque End Application: Aircraft, thunderbolt ii, a-10; aircraft, eagle f-15 Thread Diameter: 0.190 inches Grip Length: Between 0.227 inches and 0.247 inches Thready Qty Per Inch (tpi): 32 Countersink Angle: 100.0 degrees Surface Finish: 32.0 microinches threads Material: Steel comp xm-13 Material Specification: Ams 5629 assn standard single material response Thread Series Designator: Unif Shelf Life: N/a Int of Measure: - Demilitarization:	
End Application: Aircraft, thunderbolt ii, a-10; aircraft, eagle f-15 Thread Diameter: 0.190 inches Grip Length: Between 0.227 inches and 0.247 inches Thready Qty Per Inch (tpi): 32 Countersink Angle: 100.0 degrees Surface Finish: 32.0 microinches threads Material: Steel comp xm-13 Material Specification: Ams 5629 assn standard single material response Thread Series Designator: Unif Shelf Life: N/a Unit Of Measure: 	-
Aircraft, thunderbolt ii, a-10; aircraft, eagle f-15 Thread Diameter: 0.190 inches Grip Length: Between 0.227 inches and 0.247 inches Thready Qty Per Inch (tpi): 32 Countersink Angle: 100.0 degrees Surface Finish: 32.0 microinches threads Material: Steel comp xm-13 Material Specification: Ams 5629 assn standard single material response Thread Series Designator: Unjf Shelf Life: N/a Unit Of Measure: Demilitarization:	
Thread Diameter:0.190 inchesGrip Length:Between 0.227 inches and 0.247 inchesThready Qty Per Inch (tpi):32Countersink Angle:100.0 degreesSurface Finish:32.0 microinches threadsMaterial:Steel comp xm-13Material Specification:Ams 5629 assn standard single material responseThread Series Designator:UnjfShelf Life:N/aDint Of Measure:Denilitarization:	
0.190 inches Grip Length: Between 0.227 inches and 0.247 inches Thready Qty Per Inch (tpi): 32 Countersink Angle: 100.0 degrees Surface Finish: 32.0 microinches threads Material: Steel comp xm-13 Material Specification: Ams 5629 assn standard single material response Thread Series Designator: Unjf Shelf Life: N/a Unit Of Measure: 	
Grip Length: Between 0.227 inches and 0.247 inches Thready Qty Per Inch (tpi): 32 Countersink Angle: 100.0 degrees Surface Finish: 32.0 microinches threads Material: 32.0 microinches threads Material: Steel comp xm-13 Material Specification: Ams 5629 assn standard single material response Thread Series Designator: Unjf Shelf Life: N/a Unit Of Measure: 	
Between 0.227 inches and 0.247 inches Thready Qty Per Inch (tpi): 32 Countersink Angle: 100.0 degrees Surface Finish: 32.0 microinches threads Material: Steel comp xm-13 Material Specification: Ams 5629 assn standard single material response Thread Series Designator: Unif Shelf Life: N/a Unit Of Measure: Demilitarization:	
Thready Qty Per Inch (tpi): 32 Countersink Angle: 100.0 degrees Surface Finish: 32.0 microinches threads Material: Steel comp xm-13 Material Specification: Ams 5629 assn standard single material response Thread Series Designator: Unjf Shelf Life: N/a Unit Of Measure: Demilitarization:	
32 Countersink Angle: 100.0 degrees Surface Finish: 32.0 microinches threads Material: Steel comp xm-13 Material Specification: Ams 5629 assn standard single material response Thread Series Designator: Unjf Shelf Life: N/a Unit Of Measure: 	
Countersink Angle: 100.0 degrees Surface Finish: 32.0 microinches threads Material: Steel comp xm-13 Material Specification: Ams 5629 assn standard single material response Thread Series Designator: Unjf Shelf Life: N/a Unit Of Measure: 	
100.0 degrees Surface Finish: 32.0 microinches threads Material: Steel comp xm-13 Material Specification: Ams 5629 assn standard single material response Thread Series Designator: Unjf Shelf Life: N/a Unit Of Measure: Demilitarization:	
Surface Finish: 32.0 microinches threads Material: Steel comp xm-13 Material Specification: Ams 5629 assn standard single material response Thread Series Designator: Unjf Shelf Life: N/a Unit Of Measure: 	
32.0 microinches threads Material: Steel comp xm-13 Material Specification: Ams 5629 assn standard single material response Thread Series Designator: Unjf Shelf Life: N/a Unit Of Measure: Demilitarization:	-
Material:Steel comp xm-13Material Specification:Ams 5629 assn standard single material responseThread Series Designator:UnjfShelf Life:N/aUnit Of Measure:Demilitarization:	
Steel comp xm-13 Material Specification: Ams 5629 assn standard single material response Thread Series Designator: Unjf Shelf Life: N/a Unit Of Measure: 	
Material Specification:Ams 5629 assn standard single material responseThread Series Designator:UnjfShelf Life:N/aUnit Of Measure:Demilitarization:	
Ams 5629 assn standard single material response Thread Series Designator: Unjf Shelf Life: N/a Unit Of Measure: Demilitarization:	
Thread Series Designator: Unjf Shelf Life: N/a Unit Of Measure: Demilitarization:	-
Unjf Shelf Life: N/a Unit Of Measure: Demilitarization:	
Shelf Life: N/a Unit Of Measure: Demilitarization:	
N/a Unit Of Measure: Demilitarization:	
Unit Of Measure: Demilitarization:	
 Demilitarization:	
Demilitarization:	
No	
	Νο

NSN 5305-01-014-4256

Close Tolerance Screw - Page 2 of 2

Fiig: A003b0

