NSN 5305-01-014-8457

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-014-8457

| Thread Class: |
|--|
| 3a |
| Thread Direction: |
| Right-hand |
| Thread Length: |
| 1.750 inches |
| Fastener Length: |
| Between 2.031 inches and 2.125 inches |
| Head Style: |
| Pan |
| Head Diameter: |
| Between 0.306 inches and 0.322 inches |
| Head Height: |
| Between 0.105 inches and 0.115 inches |
| Internal Drive Style: |
| Torque set |
| Thread Diameter: |
| 0.164 inches |
| Thready Qty Per Inch (tpi): |
| 32 |
| Min. Tensile Strength (psi): |
| 160000 pounds per square inch |
| Product Name: |
| Navy special project |
| Screw Material: |
| Iron alloy 660 |
| Screw Material Specification: |
| Ams 5737 assn standard single material response |
| Screw Surface Treatment: |
| Passivate |
| Screw Surface Treatment Specification: |
| Qq-p-35 federal specification single treatment response |
| Thread Series Designator: |
| Unjc |
| Specification Data: |
| 80205-nas1100 professional/industrial association standard |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |

No

NSN 5305-01-014-8457 Machine Screw - Page 2 of 2

Fiig: A500d0

