NSN 5305-01-015-0657

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-015-0657 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.312 inches and 0.393 inches **Fastener Length:** Between 0.407 inches and 0.438 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.183 inches and 0.225 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.112 inches Thready Qty Per Inch (tpi): 40 Min. Tensile Strength (psi): 125000 pounds per square inch **Countersink Angle:** 100.0 degrees **Screw Material:** Steel comp 8630 or steel comp 4037 **Screw Material Specification:** Mil-s-6050 military specification 1st material response or ams 6300 assn standard 2nd material response **Screw Surface Treatment:** Cadmium and chromate **Screw Surface Treatment Specification:** Qq-p-416, type 2, cl 3 federal specification single treatment response Color: Black **Thread Series Designator:** Unjc **Specification Data:** 80205-nas514 professional/industrial association standard Shelf Life: N/a **Unit Of Measure:**

Demilitarization: No

NSN 5305-01-015-0657

Machine Screw - Page 2 of 2



Fiig:

A500d0

Mil-std (military Standard):

Mil-s-6050 spec.