NSN 5305-01-015-1232

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-015-1232 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.250 inches **Fastener Length:** Between 0.532 inches and 0.562 inches **Head Style:** Flat chamfer **Head Diameter:** 0.500 inches **Head Height:** 0.375 inches **First Diameter From Head:** Between 0.128 inches and 0.250 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.312 inches **Internal Drive Style:** Slot **Thread Diameter:** 0.164 inches Thready Qty Per Inch (tpi): **Externally Relieved Body Diameter Quantity:** 1 **Special Features:** Head vertically knurled Material: Copper alloy 360 **Material Specification:** Qq-b-626, 360 federal specification single material response **Surface Treatment:** Nickel **Surface Treatment Specification:** Mil-f-14072, -413 military specification single treatment response **Thread Series Designator:** Unc Shelf Life: N/a **Unit Of Measure:**

--

NSN 5305-01-015-1232

Externally Relieved Body Screw - Page 2 of 2



_										
וו	0	m	ш	м	•	iza	31	^	n	

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-f-14072 spec.