

View Online at <https://aerobasegroup.com/nsn/5305-01-015-3257>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.755 inches and 0.822 inches

**Fastener Length:**

Between 1.577 inches and 1.624 inches

**Head Style:**

Flat countersunk undercut

**Head Diameter:**

Between 0.928 inches and 1.016 inches

**Head Height:**

Between 0.157 inches and 0.160 inches

**Grip Diameter:**

Between 0.4990 inches and 0.4995 inches

**Internal Drive Style:**

High-torque

**Thread Diameter:**

0.500 inches

**Grip Length:**

Between 0.802 inches and 0.822 inches

**Thready Qty Per Inch (tpi):**

20

**Countersink Angle:**

100.0 degrees

**Surface Finish:**

32.0 microinches threads

**Special Features:**

Furnished with one o-ring

**Material:**

Steel comp xm-13

**Material Specification:**

Ams 5629 assn standard single material response

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0