## NSN 5305-01-015-5224

Shoulder Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-015-5224 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.303 inches and 0.323 inches **Fastener Length:** Between 0.735 inches and 0.765 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.357 inches and 0.375 inches **Head Height:** Between 0.182 inches and 0.188 inches **Shoulder Diameter:** 0.245 inches first shoulder and 0.248 inches first shoulder **Shoulder Length:** 0.370 inches first shoulder and 0.380 inches first shoulder **Internal Drive Style:** Hexagon **Thread Diameter:** 0.190 inches Width Across Flats: Between 0.125 inches and 0.127 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 160000 pounds per square inch **Shoulder Shape:** Round first shoulder **Special Features:** Knurled head optional Material: Steel **Material Specification:** Mil-h-6875 military specification single material response **Thread Series Designator:** 

**Surface Treatment:** Cadmium Unc Shelf Life: N/a

## NSN 5305-01-015-5224

Shoulder Screw - Page 2 of 2



U	n	it	Of	Μe	eas	ur	e:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-h-6875 spec.