

View Online at <https://aerobasegroup.com/nsn/5305-01-015-5686>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.512 inches and 0.625 inches

Fastener Length:

Between 0.595 inches and 0.625 inches

Head Style:

Flat chamfer

Head Diameter:

Between 0.303 inches and 0.313 inches

Head Height:

Between 0.185 inches and 0.190 inches

Internal Drive Style:

Hexagon

Thread Diameter:

0.190 inches

Width Across Flats:

Between 0.156 inches and 0.159 inches

Thready Qty Per Inch (tpi):

24

Min. Tensile Strength (psi):

80000 pounds per square inch

Hardness Rating:

80.0 rockwell b

Minimum Yield Strength:

30000 pounds per square inch

Special Features:

Finish color black

Material:

Steel comp 302 or steel comp 304 or steel comp 305 or steel comp 316 or steel comp 384 or steel

Material Specification:

66 federal standard 1st material response or 66 federal standard 2nd material response or 66 federal standard 3rd material response or 66 federal standard 4th material response or 66 federal standard 5th material response or astm a493 type xm-7 assn standard 6th material response

Surface Treatment:

Oxide

Surface Treatment Specification:

Mil-c-13924, cl 4 military specification single treatment response

Thread Series Designator:

Unc

Specification Or Standard:

6 type

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-c-13924 spec.