NSN 5305-01-015-7767

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-015-7767 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.200 inches **Fastener Length:** 0.600 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.218 inches and 0.226 inches **Head Height:** Between 0.134 inches and 0.138 inches **Hole Diameter:** 0.036 inches First Diameter From Head: Between 0.133 inches and 0.138 inches **Second Diameter From Head:** Between 0.108 inches and 0.114 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.050 inches and 0.060 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: Between 0.335 inches and 0.355 inches **Internal Drive Style:** W/o internal drive **Thread Diameter:** 0.138 inches **Hole Quantity: Hole Type:** Thready Qty Per Inch (tpi): 32 **Hole Configuration Style: Externally Relieved Body Diameter Quantity:** 2 Material:

Stainless steel

Material Specification:

Fed-std-66, comp 301 federal standard single material response

NSN 5305-01-015-7767

Mil-f-14072 spec.

Externally Relieved Body Screw - Page 2 of 2



Surface Treatment:
Passivate
Surface Treatment Specification:
Mil-f-14072, finish e300 military specification single treatment response
Thread Series Designator:
Unc
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A003b0
Mil-std (military Standard):