

View Online at <https://aerobasegroup.com/nsn/5305-01-015-9681>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.318 inches and 0.438 inches

**Fastener Length:**

Between 0.407 inches and 0.438 inches

**Head Style:**

Hexagon

**Head Height:**

Between 0.150 inches and 0.163 inches

**Width Between Flats:**

Between 0.428 inches and 0.438 inches

**Shank Unthreaded Hole Diameter:**

0.074 inches first hole and 0.082 inches first hole

**Thread Diameter:**

0.250 inches

**Thready Qty Per Inch (tpi):**

28

**Min. Tensile Strength (psi):**

150000 pounds per square inch

**Hardness Rating:**

32.0 rockwell c and 38.0 rockwell c

**Distance From Head Largest Bearing Surface To Shank Hole Center:**

0.288 inches first hole and 0.339 inches first hole

**Surface Finish:**

63.0 microinches threads

**Material:**

Steel

**Material Specification:**

Sae gr 8 assn standard single material response

**Surface Treatment:**

Phosphate

**Surface Treatment Specification:**

Mil-p-16232, ty z, cl 2 military specification single treatment response

**Thread Series Designator:**

Unf

**Specification Or Standard:**

2 type and 10p style and 8 grade

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0

**Mil-std (military Standard):**

Mil-p-16232 spec.