## NSN 5305-01-015-9684

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-015-9684

Thread Class:	
3a	
Thread Direction:	
Right-hand	
Thread Length:	
Between 0.251 inches and 0.301 inches	
Fastener Length:	
Between 3.636 inches and 3.666 inches	
Head Style:	
Flat countersunk	
Head Diameter:	
Between 0.328 inches and 0.385 inches	
Grip Diameter:	
Between 0.1885 inches and 0.1895 inches	
Internal Drive Style:	
Cross recess type 1	
Thread Diameter:	
0.190 inches	
Grip Length:	
Between 3.365 inches and 3.385 inches	
Thready Qty Per Inch (tpi):	
32	
Min. Tensile Strength (psi):	
160000 pounds per square inch	
Hardness Rating:	
40.0 rockwell c and 36.0 rockwell c	
Countersink Angle:	
100.0 degrees	
Product Name:	
Navy special project	
Material:	
Steel comp 4140 or steel comp e4340 or steel	el comp 6150 or steel comp 8735 or steel comp 8740
Material Specification:	
Mil-s-5626 military specification 1st material re	esponse or mil-s-5000 military specification 2nd material response or mil-s-8503 military
specification 3rd material response or mil-s-60	098 military specification 4th material response or mil-s-6049 military specification 5th material
response	
Surface Treatment:	
Cadmium and chromate	
Surface Treatment Specification:	

Qq-p-416, type 2, cl 2 federal specification single treatment response

## **Thread Series Designator:**

Unjf

**Specification Data:** 

## NSN 5305-01-015-9684

Close Tolerance Screw - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

## Mil-std (military Standard):

Mil-s-5626 spec.

