NSN 5305-01-016-1095

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-016-1095 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.180 inches **Fastener Length:** 0.437 inches **Head Style:** Pan **Head Diameter:** 0.263 inches **Head Height:** 0.092 inches **First Diameter From Head:** 0.138 inches **Second Diameter From Head:** 0.095 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.030 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: 0.257 inches **Internal Drive Style:** Cross recess type 1 **End Application:** An/alr-56c **Thread Diameter:** 0.138 inches Thready Qty Per Inch (tpi): 32 **Externally Relieved Body Diameter Quantity:** Material: Steel comp 302 or steel comp 303 or steel comp 304 or steel comp 305 or steel comp 316 **Material Specification:** 66 federal standard all material responses **Surface Treatment: Passivate Surface Treatment Specification:** Mil-f-14072, finish e300 military specification single treatment response

Unc

Thread Series Designator:

NSN 5305-01-016-1095

Externally Relieved Body Screw - Page 2 of 2



Mil-std (military Standard):

Mil-f-14072 spec.