

View Online at <https://aerobasegroup.com/nsn/5305-01-016-1361>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.440 inches

Fastener Length:

Between 1.640 inches and 1.687 inches

Head Style:

Hexagon

Head Height:

Between 0.140 inches and 0.172 inches

Width Between Flats:

Between 0.428 inches and 0.440 inches

Point Length:

Between 0.390 inches and 0.437 inches

Point Diameter:

0.203 inches

Point Style:

Chamfer dog

Internal Drive Style:

W/o internal drive

Thread Diameter:

0.250 inches

Thready Qty Per Inch (tpi):

28

Min. Tensile Strength (psi):

125000 pounds per square inch

Hardness Rating:

26.0 rockwell c threads and 32.0 rockwell c threads

Point Chamfer Angle:

47.0 degrees

Material:

Steel comp 4140 or steel comp 8740 or steel comp 8630 or steel comp 8735 or steel comp 4130 or steel comp 4037

Material Specification:

Mil-s-5626 military specification single material response or mil-s-6049 military specification 1st material response or mil-s-6050 military specification 2nd material response or mil-s-6098 military specification 3rd material response or mil-s-6758 military specification 4th material response or ams 6300 assn standard 5th material response

Surface Treatment:

Cadmium

Surface Treatment Specification:

Qq-p-416, type 1, cl 2 federal specification single treatment response

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-5626 spec.